

Sulfonamides – 2.1 x 20 mm Intelligent Speed Separation

Waters Corporation



This is an Application Brief and does not contain a detailed Experimental section.

Abstract

This application brief demonstrates analysis of Sulfonamides.

Introduction

The compounds analyzed in this study are:

1. Sulfadiazine
2. Sulfathiazole
3. Sulfamerazine
4. Sulfadimidine
5. Sulfamethoxazole
6. Sulfisoxazole
7. Sulfadimethoxine

Experimental

Conditions

Columns:	Atlantis dC ₁₈ , 2.1 x 20 mm IS, 3 µm, (P/N:186002058)
	Symmetry Shield RP ₁₈ , 2.1 x 20 mm IS, 3.5 µm, (P/N:186002068)
	Symmetry C ₁₈ , 2.1 x 20 mm IS, 3.5 µm, (P/N:186002066)
	XTerra MS C ₁₈ , 2.1 x 20 mm IS, 3.5 µm, (P/N:186001923)
Mobile phase A:	0.1% HCOOH in Water

Mobile phase B:	0.1% HCOOH in Methanol
Flow rate:	0.6 mL/min
Injection volume:	10 µL
Sample concentration:	20 µg/mL
Temperature:	30 °C
Detection:	UV @ 270 nm
Instrument:	Alliance 2795 with 996 PDA

Results and Discussion

Featured Products

- [Alliance HPLC System <https://www.waters.com/534293>](https://www.waters.com/534293)

WA31787.30, June 2003



© 2021 Waters Corporation. All Rights Reserved.