

Determination of Polycyclic Aromatic Hydrocarbons in Drinking Water by Liquid-Solid Extraction and High Performance Liquid Chromatography with Ultraviolet Detection

Waters Corporation



This is an Application Brief and does not contain a detailed Experimental

Determination of Polycyclic Aromatic Hydrocarbons in Drinking Water by Liquid-Solid Extraction and High Performance Liquid Chromatography with Ultraviolet Detection

section.

Abstract

In this application brief, Polycyclic aromatic hydrocarbons (PAHs) are determined in drinking water by Liquid-Solid extraction and High Performance Liquid Chromatography with Ultraviolet detection.

Introduction

Polycyclic aromatic hydrocarbons (PAHs) are one of the most wide-spread organic pollutants. PAHs are made up of fused aromatic rings and are formed during the combustion of carbon based fuels (wood, coal, diesel), as well as being present in crude oil. The United States Environmental Protection Agency (US EPA) has classified seven PAH compounds as being potentially carcinogenic including benz[a]anthra-cene, benzo[a]pyrene, benzo[b]fluoranthene, benzo[k]fluoranthene, chrysene, dibenz[a,h]anthracene, and indeno[1,2,3-cd]pyrene.

Experimental

HPLC conditions

| Instrument: | Waters Alliance HPLC system with PDA and | | |
|-------------|---|--|--|
| | fluorescence detectors | | |
| | | | |
| Eluent: | Water/acetonitrile (Table 1) | | |
| | | | |
| Column: | Waters PAH 4.6 x 250 mm (part no. 186001265) @ | | |
| | 30 °C | | |
| | | | |
| Injection: | 20 μ L of Supelco Standard EPA 610 (#48743) | | |
| | diluted 1:50 in 40:60 water/acetonitrile | | |

Determination of Polycyclic Aromatic Hydrocarbons in Drinking Water by Liquid-Solid Extraction and High Performance Liquid Chromatography with Ultraviolet Detection

| Flow Rate: | 1.2 mL/min |
|------------|---|
| Detection: | UV @ 254 nm and fluorescence using timed programmed wavelengths |
| Data: | Waters Empower software |

Sample preparation

Extract with C_{18} cartridge, elute with $MeCl_2$

Eluent preparation

Filter and degas through a 0.45 μm filter.

A: Water

B: Acetonitrile

Eluent gradient

| Time | Flow | %A | %В | Curve |
|---------|------|----|-----|-------|
| Initial | 1.2 | 40 | 60 | - |
| 12 | 1.2 | 0 | 100 | 9 |
| 23 | 1.2 | 40 | 60 | 11 |


| | Analyte | UV Max (nm) | EX (nm) | EM (nm) | Detection Limit (ppb) ¹ |
|----|-----------------------------|-------------------|------------|------------|--|
| 1 | Naphthalene | 220 | 277 | 330 | 0.14 |
| 2 | Acenaphthylene | 229 | NA | NA | NA |
| 3 | Acenaphthene | 227 | 270 | 323 | 0.01 |
| 4 | Fluorene | 261 | 265 | 310 | 0.03 |
| 5 | Phenanthrene | 251 | 252 | 365 | 0.02 |
| 6 | Anthracene | 252 | 250 | 402 | 0.01 |
| 7 | Fluoranthene | 236 | 284 | 467 | 0.02 |
| 8 | Pyrene | 240 | 332 | 378 | 0.01 |
| 9 | Benzo(a)anthracene | 287 | 284 | 390 | 0.01 |
| 10 | Chrysene | 267 | 270 | 367 | 0.04 |
| 11 | Benzo(b)fluoranthene | 256 | 298 | 436 | 0.09 |
| 12 | Benzo(k)fluoranthene | 307 | 303 | 432 | 0.01 |
| 13 | Benzo(a)pyrene ² | 296 | 280 | 410 | 0.03 |
| 14 | Dibenzo(a,h)anthracene | 297 | 294 | 398 | 0.01 |
| 15 | Benzo(g,h,l)perylene | 299 | 290 | 420 | 0.03 |
| 16 | Indeno(1,2,3-cd)pyrene | 250 | 305 | 480 | 0.49 |

¹ Fluorescence mode used for detection limit determination, no pre-concentration. Seven replicates per 40 CFR pt. 136 App. B.


² Regulated compound; action level 0.17 ppb.

Results and Discussion

PAH target analytes.



Standard chromatogram, UV @ 254 nm, 1-20 ppm PAH analytes.



Standard chromatogram, fluorescence/programmed wavelengths, 1-20 ppm PAH analytes.

Featured Products

- <u>Alliance HPLC System < https://www.waters.com/534293></u>
- Empower 3 Chromatography Data Software https://www.waters.com/10190669>
- <u>2475 Fluorescence (FLR) Detector <https://www.waters.com/514434></u>
- <u>2998 Photodiode Array (PDA) Detector https://www.waters.com/1001362</u>

720002731, August 2008

\wedge

©2019 Waters Corporation. All Rights Reserved.