Waters[™]

Application Note

Gradient Separation of Amino Acids on ACQUITY UPLC BEH HILIC

Waters Corporation

This is an Application Brief and does not contain a detailed Experimental section.

Experimental

Test Conditions

Column:	ACQUITY UPLC BEH HILIC, 2.1 x 50 mm, 1.7 μm
Part Number:	186003460
Mobile Phase A:	10 mM NH ₄ COOH, 0.2% HCOOH in 50:50 ACN: H ₂ O
Mobile Phase B:	10 mM NH ₄ COOH, 0.2% HCOOH in 90:10 ACN: H ₂ O
Flow Rate:	0.529 mL/min
Injection Volume:	5.0 µL
Sample Concentration:	5 μg/mL

Sample Diluent:	73:25:2 ACN:MeOH:H $_2$ O with 0.2% HCOOH and
	5 μM HCl
Temperature:	30 C
Instrument:	Waters ACQUITY UPLC with SQ Mass Detector

Gradient:


Time (min)	%A	%В
0.0	0.1	99.9
1.65	0.1	99.9
4.49	99.9	0.1
4.54	0.1	99.9
5.05	0.1	99.9

MS Conditions


Ionization Mode:	ES ⁺
Capillary:	3.0 kV
Cone:	20 V
Extractor:	3 V
RF Lens:	0.3 V
Source Temperature:	150 °C


Desolvation Temperature:	350 °C
Cone Gas Flow:	50 L/Hr
Desolvation Gas Flow:	700 L/Hr
SIR:	136.1 m/z Homocysteine
	150.2 m/z Methionine

Methionine



Homocysteine





Featured Products

1.0

ACQUITY UPLC System <https://www.waters.com/514207>

SQ Detector 2 <https://www.waters.com/134631584>

2.0

3.0

4.0

5.0 min

Available for Purchase Online

ACQUITY UPLC BEH HILIC Column, 130Å, 1.7 µm, 2.1 mm X 50 mm, 1/pkg < https://www.waters.com/waters/partDetail.htm?cid=511505&id=28049>

WA60134, August 2009

©2019 Waters Corporation. All Rights Reserved.