


Gradient Separation of Catecholamines on Atlantis HILIC Silica

日本ウォーターズ株式会社



This is an Application Brief and does not contain a detailed Experimental section.

Abstract

This application brief describes the gradient separation of catecholamines on Atlantis HILIC Silica column.

Introduction

The compounds used in this study are:

1. Norepinephrine (NE)
2. Epinephrine (E)
3. 3-Hydroxytyramine (Dopamine)

Experimental

Test Conditions

Column:	Atlantis HILIC Silica, 4.6 x 50 mm, 5 µm
Part Number:	186002028
Mobile Phase A:	H ₂ O
Mobile Phase B:	ACN
Mobile Phase C:	200 mM NH ₄ COOH, pH 3.0
Flow Rate:	2.0 mL/min
Injection Volume:	5.0 µL
Sample Diluent:	75:25 ACN:MeOH with 0.2% FA
Sample Concentration:	42 µg/mL Norepinephrine (NE), 17 µg/mL Epinephrine (E), 83 µg/mL 3-hydroxytyramine (Dopamine)
Detection:	UV @ 280 nm

Temperature:

Ambient

Instrument:

Waters Alliance System, 2695 Separations
Module with 2996 PDA

Gradient:




Time(min)	Profile
-----------	---------

	%A
--	----

0.0	0
-----	---

5.0	25
-----	----

Results and Discussion



Featured Products

Alliance HPLC System <<https://www.waters.com/534293>>

WA64073, August 2009

©2019 Waters Corporation. All Rights Reserved.